



new brake technology

# High expectations: 2014 STOP with confidence


Formula introduces two new brakes in 2014 featuring the newest in innovative technology. Known for more than 25 years for our forward thinking design, we are proud to introduce the Cartridge System in our new C1 brake as well as the Pull Master Cylinder in our new top of the line R1 Racing brake.

Paired with our proven Enhanced Caliper Technology Formula brakes are once more the top of the line choice when it comes to power, technology and design.



# R1 Racing pull master cylinder technology

- Piston is pulled instead of pushed through the bore resulting in less friction and more durability.
- Compact design improves ergonomics & kinematics.
- New body design drops weight by more than 15g.
- High volume reservoir with composite cap.




C1 master cylinder cartridge technology

- Increased Roll back for easier mounting and greater pad clearance.
- Suitable for small hands thanks to a reduced minimum lever distance from the handlebar.
- Improved ergonomics.
- Axial master cylinder for a more progressive feel.
- Innovative cartridge system for easy maintenance and long life.
- Increased hydraulic ratio: more power and responsiveness.

# Proven ECT Enhanced Caliper Technology

- Increased rollback of the brake pads.
- Easy rub-free brake installation.



 $\mathsf{Z}$ 



the world's lightest disc brake













MixMaster





ECT Enhanced Caliper Technology

Formula's **R1 Racing** once again redefines ultra light disc brakes for 2014 with its revolutionary new pull master cylinder.

With titanium hardware, kevlar braided hose, and composite reservoir cap dropping the weight to 267g, the **R1 Racing** is the lightest disc brake in the market.

#### MASTER CYLINDER

**FEATURES** 

Forged radial pull master cylinder

Removable handlebar clamp

Flip-flop master cylinder

Composite reservoir cap

Hard anodized master cylinder piston

High capacity reservoir

Laser etched logos

#### CALIPER

Forged one-piece caliper with 22 mm pistons

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology - Increased pad roll back (simplifying installation) - Increased fluid capacity

#### SPECIFICATION

| MC body      | Polished and anodized                                         |
|--------------|---------------------------------------------------------------|
| Caliper body | Polished and anodized with black cap                          |
| Lever blade  | Forged aluminum lever blade                                   |
| Hose         | Kevlar: 100cm front / 165cm rear                              |
| Brake pads   | Semi-metallic w / Aluminum back plate                         |
| Mounting     | PM6"                                                          |
| Hardware     | Titanium                                                      |
| Weight       | 267g ( 85cm hose, 160mm 1-piece rotor and mounting hardware ) |

#### OPTION

| 1-piece rotor 6 bolt IS<br>or Center Lock | 160mm / 180mm / 203mm                                                                   |
|-------------------------------------------|-----------------------------------------------------------------------------------------|
| 2-piece rotor 6 bolt IS                   | Red or black - 140mm / 160mm / 180mm / 203mm                                            |
| 2-piece rotor center lock                 | Red or black - 160mm / 180mm                                                            |
| Adapters                                  | IS and PM: 140mm / 160mm / 180mm / 203mm                                                |
| FCS                                       | Feeling Control System. Available in red, black and gold                                |
| MixMaster                                 | Custom shifter mounting perch for SRAM shifters                                         |
| SpeedLock                                 | Hose quick connect - mount to caliper, master cylinder, or inline - red, black and gold |

FCS



Formula's no nonsense DH brake, the **RO** combines the greatest stopping power with the elegant looks of Italian design. The oval piston technology allows for a compact caliper design while increasing the piston size compared to the T1 by 15%. The **RO** sets the standard for brake power.

#### **MASTER CYLINDER**

Forged "semi" radial master cylinder improves ergonomics and lever ratio

High capacity reservoir

Removable handlebar clamp

Flip-flop master cylinder

Forged lever blade with integrated TFRA (Tool Free Reach Adjust)

Hard anodized master cylinder piston

Laser etched logos

#### CALIPER

Forged one-piece caliper with 24 x 25.4mm pistons

Unique Oval Piston Technology

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology - Increased pad roll back (simplifying installation)
- Increased fluid capacity

#### SPECIFICATION

| MC body      | Polished and anodized                                       |  |  |  |
|--------------|-------------------------------------------------------------|--|--|--|
| Caliper body | Polished and anodized with black cap                        |  |  |  |
| Lever blade  | Forged aluminum, anodized gloss black                       |  |  |  |
| FCS          | Feeling Control System - black                              |  |  |  |
| TFRA         | Tool Free Reach Adjust - integrated into lever              |  |  |  |
| Hose         | Black: 100cm front / 165cm rear                             |  |  |  |
| Brake pads   | Sintered compound                                           |  |  |  |
| Mounting     | PM6"                                                        |  |  |  |
| Weight       | 360g (85cm hose, 160mm 1-piece rotor and mounting hardware) |  |  |  |

#### OPTION

| ever blade                               | Carbon - 6g less than aluminium                                                        |  |  |  |
|------------------------------------------|----------------------------------------------------------------------------------------|--|--|--|
| -piece rotor 6 bolt IS or<br>Center Lock | 160mm / 180mm / 203mm                                                                  |  |  |  |
| 2-piece rotor 6 bolt IS                  | Red or black - 140mm / 160mm / 180mm / 203mm                                           |  |  |  |
| 2-piece rotor center lock                | Red or black - 160mm / 180mm                                                           |  |  |  |
| Hardware                                 | Titanium caliper and rotor bolts - 10g less than steel                                 |  |  |  |
| Adapters                                 | IS and PM: 140mm / 160mm / 180mm / 203mm                                               |  |  |  |
| MixMaster                                | Custom shifter mounting perch for SRAM shifters                                        |  |  |  |
| SpeedLock                                | Hose quick connect - mount to caliper, master cylinder or inline - red. black and gold |  |  |  |



Formula's flagship, the R1 sets the standard for XC and All-Mountain brakes. Despite its low weight, it delivers amazing enduro worthy stopping power for All Mountain and 29er applications.

#### **MASTER CYLINDER**

Forged radial master cylinder

Removable handlebar clamp

Flip-flop master cylinder

Forged lever blade with integrated TFRA (Tool Free Reach Adjust)

Hard anodized master cylinder piston

High capacity fluid reservoir

Laser etched logos

#### CALIPER

Forged one-piece caliper with 22mm pistons

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology - Increased pad roll back (simplifying installation) - Increased fluid capacity

#### **SPECIFICATION**


| MC body      | Anodized gloss black                                        |
|--------------|-------------------------------------------------------------|
| Caliper body | Anodized gloss black with red cap                           |
| ever blade   | Forged aluminum, anodized gloss black                       |
| ΓFRA         | Tool Free Reach Adjust - integrated into lever              |
| Hose         | Black: 100cm front / 165cm rear                             |
| Brake pads   | Semi-metallic w/ Aluminum back plate                        |
| Mounting     | PM6"                                                        |
| Weight       | 296g (85cm hose, 160mm 1-piece rotor and mounting hardware) |

#### OPTION

| Lever blade                               | Carbon - 6g less than aluminium                                                        |
|-------------------------------------------|----------------------------------------------------------------------------------------|
| 1-piece rotor 6 bolt IS or<br>Center Lock | 160mm / 180mm / 203mm                                                                  |
| 2-piece rotor 6 bolt IS                   | Red or black - 140mm / 160mm / 180mm / 203mm                                           |
| 2-piece rotor center lock                 | Red or black - 160mm / 180mm                                                           |
| Hardware                                  | Titanium caliper and rotor bolts - 10g less than steel                                 |
| Adapters                                  | IS and PM: 140mm / 160mm / 180mm / 203mm                                               |
| FCS                                       | Feeling Control System Available in red, black and gold                                |
| MixMaster                                 | Custom shifter mounting perch for SRAM shifters                                        |
| SpeedLock                                 | Hose quick connect - mount to caliper, master cylinder or inline - red, black and gold |

ECT Enhanced Caliper Technology

# most versatile















Formula's **T1** has garnered a worldwide reputation as the best in its class. Bike Tipp™, Best of MTBR and many other accolades have been bestowed upon the T1.

#### MASTER CYLINDER

**FEATURES** 

Forged radial master cylinder

Removable handlebar clamp

Flip-flop master cylinder

Forged lever blade with integrated TFRA (Tool Free Reach Adjust)

Hard anodized master cylinder piston

High capacity fluid reservoir

Laser etched logos

SPECIFICATION

#### CALIPER

Redesigned caliper body with improved hose routing

3D forged one-piece caliper body with 24mm pistons

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology
- Increased pad roll back

- (simplifying installation)
   Increased fluid capacity

| MC body      | Anodized gloss black                              |  |  |
|--------------|---------------------------------------------------|--|--|
| Caliper body | Anodized gloss black with gold cap                |  |  |
| Lever blade  | Forged aluminum, anodized gloss black             |  |  |
| FCS          | Feeling Control System - gold                     |  |  |
| TFRA         | Tool Free Reach Adjust - integrated into lever    |  |  |
| Hose         | Black: 100cm front / 165cm rear                   |  |  |
| Brake pads   | Sintered compound                                 |  |  |
| Mounting     | PM6"                                              |  |  |
| Weight       | 335g (85cm hose, 160mm 1-piece rotor and mounting |  |  |

hardware)

#### OPTION Lever blade Carbon - 6g less than aluminum 1-piece rotor 6 bolt IS 160mm / 180mm / 203mm or Center Lock 2-piece rotor 6 bolt IS Red or black - 140mm / 160mm / 180mm / 203mm Red or black - 160mm / 180mm 2-piece rotor center lock Hardware Titanium caliper and rotor bolts - 10g less than steel Adapters IS and PM: 140mm / 160mm / 180mm / 203mm MixMaster Custom shifter mounting perch for SRAM shifters Hose quick connect - mount to caliper, master SpeedLock cylinder or inline - red, black and gold













best value













Tool Free Reach Adjust





ECT Enhanced Caliper Technology

Formula's **RX** is a perfect all-rounder at a great price. This brake steps ahead of the competition with its new standard features: FCS and TFRA making it a great value with exceptional performance.

#### **MASTER CYLINDER**

High capacity reservoir

Removable handlebar clamp

Flip-flop master cylinder

Hard anodized master cylinder piston

Laser etched logos

**FEATURES** 

#### CALIPER

One-piece caliper with 22mm pistons

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology - Increased pad roll back (simplifying installation) - Increased fluid capacity

| SPECIFICATION                             |                                                                                        |  |  |  |
|-------------------------------------------|----------------------------------------------------------------------------------------|--|--|--|
| MC body                                   | Painted gloss black                                                                    |  |  |  |
| Caliper body                              | Painted gloss black with red cap                                                       |  |  |  |
| Lever blade                               | Forged Aluminium, anodized matte black                                                 |  |  |  |
| Hose                                      | Black: 100cm front / 165cm rear                                                        |  |  |  |
| FCS                                       | Feeling Control System Available in red                                                |  |  |  |
| TFRA                                      | Tool Free Reach Adjust - Forged aluminum lever blade w/ integrated red dial            |  |  |  |
| Brake pads                                | Semi-metallic compound                                                                 |  |  |  |
| Mounting                                  | PM6"                                                                                   |  |  |  |
| Weight                                    | 337g (85cm hose, 160mm 1-piece rotor and mounting hardware)                            |  |  |  |
| OPTION                                    |                                                                                        |  |  |  |
| 1-piece rotor 6 bolt IS or<br>Center Lock | 160mm / 180mm / 203mm                                                                  |  |  |  |
| 2-piece rotor 6 bolt IS                   | Red or black - 140mm / 160mm / 180mm / 203mm                                           |  |  |  |
| 2-piece rotor center lock                 | Red or black - 160mm / 180mm                                                           |  |  |  |
| Hardware                                  | Titanium caliper and rotor bolts - 10g less than steel                                 |  |  |  |
| Adapters                                  | IS and PM: 140mm / 160mm / 180mm / 203mm                                               |  |  |  |
| MixMaster                                 | Custom shifter mounting perch for SRAM shifters                                        |  |  |  |
| SpeedLock                                 | Hose quick connect - mount to caliper, master cylinder or inline - red, black and gold |  |  |  |

12



ECT Enhanced Caliper Technology

The Formula **C1** is new for 2014. This versatile brake, with Formula's new cartridge technology, is easy to maintain and provides great performance and value at a weight below 346g.

#### **MASTER CYLINDER**

MCCT: Master Cylinder Cartridge Technology

High capacity reservoir

Removable handlebar clamp

Flip-flop master cylinder

Hard anodized master cylinder piston

Laser etched logos

#### CALIPER

One-piece post mount caliper body with 22mm pistons

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology - Increased pad roll back (simplifying installation) - Increased fluid capacity

#### **SPECIFICATION**

| MC body      | Painted gloss black / white                                                          |
|--------------|--------------------------------------------------------------------------------------|
| Caliper body | Painted gloss black with silver cap<br>Painted gloss white with black cap            |
| Lever blade  | Aluminum anodized gloss black (black MC)<br>Aluminum anodized matte black (white MC) |
| Hose         | Black: 100cm front / 165cm rear                                                      |
| Brake pads   | Semi-metallic compound                                                               |
| Mounting     | PM6"                                                                                 |
| Weight       | 337g (85cm hose, 160mm 1-piece rotor and mounting hardware)                          |
|              |                                                                                      |

#### OPTION


| -piece rotor 6 bolt IS or<br>Center Lock | 160mm / 180mm / 203mm                                  |
|------------------------------------------|--------------------------------------------------------|
| 2-piece rotor 6 bolt IS                  | Red or black - 140mm / 160mm / 180mm / 203mm           |
| 2-piece rotor center lock                | Red or black - 160mm / 180mm                           |
| Hardware                                 | Titanium caliper and rotor bolts - 10g less than steel |
| Adapters                                 | IS and PM: 140mm / 160mm / 180mm / 203mm               |
| MixMaster                                | Custom shifter mounting perch for SRAM shifters        |
| SpeedLock                                | Hose quick connect inline - red, black and gold        |

# **ROTORS**



# **ROTOR DIAMETER**

| 2-PIECE ROTOR                 |     |     |     |     |
|-------------------------------|-----|-----|-----|-----|
| Aluminium Carrier 6 holes     |     |     |     |     |
| Diameter (mm)                 | 140 | 160 | 180 | 203 |
| Weight (grams)                | 78  | 95  | 115 | 139 |
| Aluminium Carrier Center Lock |     |     |     |     |
|                               |     |     |     |     |









# ROTOR DIAMETER

| 1-PIECE ROTOR SL              |     |     |     |  |
|-------------------------------|-----|-----|-----|--|
| Stainless Steel               |     |     |     |  |
| Diameter (mm)                 | 160 | 180 | 203 |  |
| Weight (grams) 87 123 157     |     |     |     |  |
| Stainless Steel w/Center Lock |     |     |     |  |
| Diameter (mm)                 | 160 | 180 | 203 |  |
| Weight (grams)                | 106 | 141 | 176 |  |






- Lateral stiffness increased by 40%.
- Heat exchange increased.
- The increased lateral stiffness reduces noise vibration.

1-PIECE ROTOR >

# ROTOR DIAMETER

| IL I LIV   |                                 |                                            |
|------------|---------------------------------|--------------------------------------------|
|            |                                 |                                            |
|            |                                 |                                            |
| 160        | 180                             |                                            |
| 101        | 126                             |                                            |
| //Center I | -ock                            |                                            |
| 160        | 180                             |                                            |
| 120        | 145                             |                                            |
|            | 160<br>101<br><b>//Center I</b> | 160 180<br>101 126<br><b>//Center Lock</b> |



## **OPTIONS**

#### FCS (FEELING CONTROL SYSTEM)

The **FCS** valve is available for all 2014 FORMULA brakes (except on C1 and standard on RO, T1, and RX). It allows for an adjustment of the lever's contact-point (free-throw) to suit the rider's personal preference and ergonomic needs. The FCS is available in anodized red, gold or black.

#### LEVER INTEGRATED TFRA (Tool Free Reach Adjust)

Standard on the R1, T1, RO, and RX (not available on C1), this easy to use feature allows a tool-free adjustment of the lever reach (resting position) to suit the rider's personal preference. The **TFRA** adjustment knob is integrated into the lever for increased durability and is available in anodized **red**, **gold**, or **silver**. The **TFRA** lever blade has the same ergonomics as the standard lever blade.

#### **BRAKE ROTORS** WITH ALUMINIUM SPIDERS

Optional for all 2014 FORMULA brakes are our two-piece rotors with aluminum spiders. These brake rotors are available for both centerlock (160 & 180mm only) and 6 bolt pattern in 140mm, 160mm, 180mm, and 203mm.

The FORMULA Centerlock adapter is available to install our one-piece rotor to a Centerlock hub. Available colors are **black** and **red**.

#### MIXMASTER

Optional for all 2014 FORMULA brakes, the MixMaster clamp allows direct integration of various shifters to the brake for better ergonomics and a clean look on your handlebar.

#### SPEED LOCK

The **SpeedLock** is the revolutionary feature for your brake hose. An easy click connects and disconnects the hose from caliper or master cylinder - without losing a drop of brake fluid it makes internal hose routing an easy task.

This feature is available in three options and four colors (black, gold, and red) and can be used on all Formula brakes.

#### THREE VERSIONS AVAILABLE:

- A) In-line
- B) At the caliper
- C) At the master cylinder







# FORMULA recommends to use Shell Donax DOT 4 ULTRA Brake Fluid.



Formula now utilizes radial and axial master cylinder bodies and one piece calipers for 2014.

Our patented master cylinder piston design allows us to design a compact, lightweight, and very powerful brake. With the primary cup fixed to the master cylinder body we supply you with a very durable master cylinder compared to conventional designs.

Formula brakes are easy to customize with our upgrade options:

- FCS Feeling Control System.
- TFRA Tool Free Reach Adjust.
- MixMaster shifter perch.
- SpeedLock hydraulic quick connect.
- Titanium Hardware.
- Carbon Lever Blade.

#### **DOT 4 BRAKE FLUID**

All Formula brakes are designed for use with DOT 4 fluid. DOT 4 has a higher boiling point than mineral oil and is less hygroscopic than DOT 5.1 and therefore increases fade resistance. DOT 4 is safe on all Formula seals and aluminum parts.






# New Generation of Suspension FORKS DROP-In cartridge system



#### INNOVATIVE FEATURES OF THE THIRTYFIVE

- **1. Directional Floating Seal (D.F.S.)**This technology provides an extra tight seal even at the moment of maximum fork flex.
- 2. Satellite Switch Adjustment (S.S.A.)

  This feature allows compression, lockout and lockout threshold controls to be placed on one side of the fork crown which gives the rider the possibility to adjust each individual function rapidly.
- **3. Cap Directional Control (C.D.C.)**This allows the rider to rotate the orientation of the S.S.A., according to individual preference.
- **4. Lockout Force Adjustment (L.F.A.)**The lockout threshold adjustment allows the adjustment of the rigidity of the lockout setting separate from the main lockout and also incorporates a safety blow off valve.



# 

26" QR9 / 26" 15QR



Air adjustment









Formula's **THIRTYTHREE** line of suspension forks was developed with World Championship experience on the roughest and fastest XC courses on the globe. The **THIRTYTHREE** forks feature custom developed low-friction polymeric bushings to ensure buttery smooth function and minimize the impact of excessive seal friction found in many air spring forks.

Compression and rebound damping adjustments allow for precise setup. Our unique lockout with integrated blow-off threshold allows you to custom tune your **THIRTYTHREE** to fit your specific needs.

| WEIGHTS 26" QR9 (a)                      |                       |  |
|------------------------------------------|-----------------------|--|
| straight steerer 1 1/8"                  | 1443 g <sup>(b)</sup> |  |
| tapered steerer 1 1/8"- 1.5"             | 1477 g <sup>(b)</sup> |  |
| WEIGHTS 26" 15TA                         |                       |  |
| WEIGHTS 26" 15TA                         |                       |  |
| WEIGHTS 26" 15TA straight steerer 1 1/8" | 1517 g <sup>(b)</sup> |  |

(a) 27.5" compatible: 696 maximum wheel diameter.(b) with steerer tube.

## **SPECIFICATION**

- 33mm hard anodized 7000 aluminum stanchions
- Magnesium lowers w/ PM6 brake mount
- FORMULA control closed cartridge damping 7 adjustments + 2 lockout settings
- FORMULA rebound 18 adjustments
- Air spring w/ Dual Coil Technology
- HPV (high-pressure valve): blow off valve prevents damage when fork is locked out
- Polymeric bushings offer low weight and less friction
- Lock Out: crown mounted standard or remote option
- ILS (Integrated Locking System): tool free 15QR axles
- Travel: 26" 85-120mm

## **COLOR**

| Black |  |
|-------|--|
| White |  |

| 15TA                     | 55 g |
|--------------------------|------|
| QR (for 15TA)            | 26 g |
| Remote Lockout in option | 90 g |

22

# FORMULA 35

27.5" / 29" 15QR







Rebound adjustment





#### **FEATURES**

The **THIRTYFIVE** fork drops onto the trail with a new self contained damping cartridge.

In the shop the **THIRTYFIVE**'s cartridge system is serviceable without the need to remove the fork from the bike making routine maintenance quick and easy.

On the trail the Satellite Switch Adjustment (S.S.A.) keeps your controls in one place making for easy on the fly tuning of compression, lockout and lockout threshold. With the perfect travel options, rebound and an air spring round out the **THIRTYFIVE**'s adjustments.

| WEIGHTS 27.5"                 |                       |
|-------------------------------|-----------------------|
| tapered steerer 1 1/8" - 1.5" | 1650 g <sup>(b)</sup> |
|                               |                       |
| WEIGHTS 29"                   |                       |

(b) with steerer tube.

#### **SPECIFICATION**

- 35mm hard anodized 7000 aluminum stanchions
- Magnesium lowers w/ PM6 brake mount
- Easy removable damping cartridge with lockout, lockout threshold, and compression adjustment
- FORMULA rebound
- Air spring w/ Dual Coil Technology
- HPV (high-pressure valve): blow off valve prevents damage when fork is locked out
- Low friction polymeric bushings
- Tapered steerer and 15TA axle
- Lock Out: crown mounted standard or handlebar mounted remote lockout
- Travel 27.5": 100 160mm

29": 100 - 140mm

#### **COLOR**

| Black |
|-------|
| White |

| 15TA                               | 55 g |
|------------------------------------|------|
| QR (for 15TA)                      | 26 g |
| Hydraulic Remote Lockout in option | 70 g |

24






Formula is proud to offer the **XC HYPERLIGHT 26"** tubular race wheelset. The weight, stiffness, and responsiveness of this wheelset is changing the world of XC racing. Carbon rims combined with our lightweight 3D forged hubs drop the weight to only 1191g. Accelerating away from your competition has never been easier.

| WEIGHTS 26" |       |
|-------------|-------|
| Front QR9   | 530 g |
| Front 15TA  | 510 g |
| Rear QR9    | 681 g |
| Rear X12 TA | 660 g |

#### **SPECIFICATION**

- 24 straight pull double butted spokes laced 2 cross with alloy nipples
- 3K Carbon Tubular Rim
- CNC machined and anodized 7000 aluminum hub
- Ultra-light CNC machined and anodized 4-pawl freehub body
- External Bearing Technology: Rear hub's load carrying cartridge bearing located outboard of freehub body for increased durability and load distribution
- Front axle options: QR9 or 15TA
- Rear axle: QR9 or 12/142 (X12 TA)
- QR9 Skewers: Titanium front: 32g / rear: 34g
- Recommended tire size: 1.8" 2.25"
- XD-Driver Free Hub Body
- Shimano Free Hub Body

| Hub | Black  |
|-----|--------|
| Rim | Carbon |







#### THE ULTIMATE NO EXCUSE XC RACE WHEELSET.

Utilizing a 17mm wide scandium rim, straight-pull aero spokes, alloy nipples and feature rich hubs.


**XC SUPERLIGHT** wheels are light, fast, responsive, and the ideal upgrade for any rider looking to fly.

| WEIGHTS 26" |       |
|-------------|-------|
| Front QR9   | 599 g |
| Front 15TA  | 579 g |
| Rear QR9    | 764 g |

#### **SPECIFICATION**

- 24 straight pull aero spokes laced 2 cross with alloy nipples
- 17mm Scandium rim
- 3D forged and anodized 7000 aluminum hub
- Ultra-light 3D forged and anodized 4-pawl freehub body
- External Bearing Technology: Rear hub's load carrying cartridge bearing located outboard of freehub body for increased durability and load distribution
- Front axle options: QR9 or 15TA
- Rear axle: QR9
- QR9 Skewers: Titanium front: 32g / rear: 34g
- Recommended tire size: 1.0" 2.2"
- Shimano Free Hub Body

| Hub | Red                  |
|-----|----------------------|
| Rim | Black - Bead Blasted |







#### THE ULTIMATE NO EXCUSE XC RACE WHEELSET.

A 17mm wide scandium rim, straight-pull bladed spokes, alloy nipples and feature rich hubs.

**XC SUPERLIGHT** wheels are light, fast, responsive, and the ideal upgrade for any rider looking to fly.


| WEIGHTS 27.5" |       |  |
|---------------|-------|--|
| Front QR9     | 536 g |  |
| Front 15TA    | 616 g |  |
| Rear QR9      | 808 g |  |
| Rear X12 TA   | 787 g |  |

| WEIGHTS 29" |       |
|-------------|-------|
| Front QR9   | 650 g |
| Front 15TA  | 630 g |
| Rear QR9    | 814 g |
| Rear X12 TA | 793 g |

#### **SPECIFICATION**

- 24 straight pull double butted spokes laced 2 cross with alloy nipples
- 17mm Scandium rim
- CNC machined and anodized 7000 aluminum hub
- Ultra-light CNC machined and anodized 4-pawl freehub body
- External Bearing Technology: Rear hub's load carrying cartridge bearing located outboard of freehub body for increased durability and load distribution
- Front axle options: QR9 or 15TA
- Rear axle: QR9 or 12/142 (X12 TA)
- QR9 Skewers: Titanium front: 32g / rear: 34g
- Recommended tire size: 1.0" 2.2"
- XD-Driver Free Hub Body
- Shimano Free Hub Body

| Hub | Black                |
|-----|----------------------|
| Rim | Black - Bead Blasted |







With fast growing demand of 29er trail bikes the need for a stiffer, durable, and reliable wheelset that doesn't come with big weight penalties became obvious.

Formula delivers with the VOLO XC LIGHT 29" wheelset. 21mm inner width scandium rims a stiffness to weight ratio that exceeds all other non carbon rimmed wheels. With the same feature rich hubs found on the rest of our XC wheel lineup, this wheelset is designed as much for bombing down the trails as it is for flying up.

The **VOLO XC LIGHT** is also available in 26", 27.5" and 29".

| WEIGHTS 26" |       |
|-------------|-------|
| Front QR9   | 673 g |
| Front 15TA  | 652 g |
| Rear QR9    | 858 g |
| Rear X12 TA | 837 g |


| WEIGHTS 27.5" |  |
|---------------|--|
| 709 g         |  |
| 689 g         |  |
| 871 g         |  |
| 850 g         |  |
|               |  |

| WEIGHTS 29" |       |
|-------------|-------|
| Front QR9   | 721 g |
| Front 15TA  | 701 g |
| Rear QR9    | 884 g |
| Rear X12 TA | 863 g |

# **SPECIFICATION**

- 24 straight pull double butted spokes laced 2 cross with alloy nipples
- 21mm Scandium rim
- CNC machined and anodized 7000 aluminum hub
- Ultra-light CNC machined and anodized 4-pawl freehub body
- External Bearing Technology: Rear hub's load carrying cartridge bearing located outboard of freehub body for increased durability and load distribution
- Front axle options: QR9 or 15TA
- Rear axle: QR9 or 12/142 (X12 TA)
- QR9 Skewers: Titanium front: 32g / rear: 34g
- Recommended tire size: 1.5" 2.5"
- XD-Driver Free Hub Body
- Shimano Free Hub Body

| Hub | Black                    |
|-----|--------------------------|
| Rim | Champagne - Bead blasted |









AM LIGHT 26" / 27.5" / 29"



## **FEATURES**

With the **VOLO All-Mountain Light**, Formula completes its product range of light weight competition wheel sets. The front wheel is equipped with a CNC machined oversized and "Formula Triple Axle Technology." that easily adjusts to varying standards - QR9, 15TA and 20TA. The rear wheel features X12 axle and external bearing technology for exceptional strength.

At just 1673 grams these wheels easily climb and tackle any obstacle on the way down.

| WEIGHTS 26" |       |
|-------------|-------|
| Front QR9   | 788 g |
| Front 15TA  | 765 g |
| Front 20TA  | 749 g |
| Rear QR9    | 929 g |
| Rear X12 TA | 908 g |


| WEIGHTS 27.5" |       |
|---------------|-------|
| Front QR9     | 819 g |
| Front 15TA    | 797 g |
| Front 20TA    | 782 g |
| Rear QR9      | 959 g |
| Rear X12 TA   | 937 g |

| WEIGHTS 29" |       |
|-------------|-------|
| Front QR9   | 831 g |
| Front 15TA  | 808 g |
| Front 20TA  | 792 g |
| Rear QR9    | 972 g |
| Rear X12 TA | 951 g |

# **SPECIFICATION**

- 24 straight pull double butted spokes laced 2 cross with brass nipples
- 21mm Scandium rim
- CNC machined oversized hub with FORMULA Triple Axle Technology and hard anodized 4-pawl freehub body
- External Bearing Technology: Rear hub's load carrying cartridge bearing located outboard of freehub body for increased durability and load distribution
- Front axle options: QR9 / 15TA / 20TA
- Rear axle: QR9 or 12X142 (X12 TA)
- QR9 Skewers: Titanium front: 32g / rear: 34g
- Recommended tire size: 1.5" 2.5"
- XD-Driver Free Hub Body
- Shimano Free Hub Body

| Hub | Black                    |
|-----|--------------------------|
| Rim | Champagne - Bead blasted |







# street performance





ECT Enhanced Caliper Technology

Formula introduces the first fully integrated hydraulic disc brake for road bikes, the RR1. The new brake system integrates the hydraulic reservoir in its aluminum lever body and is compatible with Dura-Ace Di2 and Campagnolo EPS.

A strong, forged, post mount caliper with 22mm-pistons combined with a 2-piece 140mm rotor provides the perfect amount of power, control and modulation.

#### MASTER CYLINDER

Forged radial master cylinder

Removable handlebar clamp

Forged lever blade

Hard anodized master cylinder piston

High capacity fluid reservoir

#### CALIPER

Forged one-piece caliper with 22mm pistons

Top and bottom vented caliper body for maximum cooling and performance

Top loading pads simplify pad changes

Laser etched logos

ECT: Enhanced Caliper Technology

- Increased pad roll back (simplifying installation)
   Increased fluid capacity

#### **SPECIFICATION**

| Caliper body | White painted with black cap                                |
|--------------|-------------------------------------------------------------|
| Lever blade  | Forged aluminum, anodized gloss black                       |
| Hose         | White: 100cm front / 165cm rear                             |
| Brake pads   | Semi-metallic w/ Aluminum back plate                        |
| Mounting     | PM compatible                                               |
| Weight       | 320g (85cm hose, 140mm 2-piece rotor and mounting hardware) |

#### OPTION

| Lever blade             | Carbon - 14g less than aluminium                |
|-------------------------|-------------------------------------------------|
| 2-piece rotor 6 bolt IS | Black - 140mm / 160mm                           |
|                         | Hose quick connect inline - red, black and gold |

38



Introducing the newest in Italian wheel design - the Formula RR1 high performance disc brake road wheel set! The RR1 features a durable trail tested hub capable of competition level performance and an aero full carbon rim available in tubular.

The ultra-light tubular 45 is not held back by rim brake designs - reducing rotational weight - for increased acceleration.

#### WEIGHTS

#### **CARBON TUBULAR 45**

| Front QR9  | 603 g |
|------------|-------|
| Front 15TA | 583 g |
| Rear QR9   | 771 g |

#### **SPECIFICATION**

- 24 straight pull double butted spokes laced 2 cross w/ self-locking black alloy nipples
- CNC machined and anodized 7000 aluminum hub
- Ultralight CNC machined and anodized 4 pawl freehub body with 6° engagement
- Titanium QR9 skewers: front 32g / rear 34g
- Recommended tire width: 19-28mm
- Rim: Carbon Tubular 45: disc brakes only

# COLOR

| Hub | Black  |  |
|-----|--------|--|
| Rim | Carbon |  |

## **OPTIONS**

Front axle options: QR9 & 15TA





Introducing the newest in Italian wheel design - the Formula RR1 high performance disc brake road wheel set! The RR1 features a durable trail tested hub capable of competition level performance and an aero full carbon rim available in tubular or clincher.

#### **WEIGHTS**

#### CARBON CLINCHER 50

| Front QR9  | 732 g |
|------------|-------|
| Front 15TA | 712 g |
| Rear QR9   | 900 g |

#### **CARBON TUBULAR 50**

| Front QR9  | 684 g |  |
|------------|-------|--|
| Front 15TA | 664 g |  |
| Rear QR9   | 852 g |  |

#### **SPECIFICATION**

- 24 straight pull double butted spokes laced 2 cross w/ self-locking black alloy nipples
- CNC machined and anodized 7000 aluminum hub
- Ultralight CNC machined and anodized 4 pawl freehub body with 6° engagement
- Titanium QR9 skewers: front 32g / rear 34g
- Recommended tire width: 19-28mm
- Rim:
  - Carbon Clincher 50: rim and disc brakes
  - Carbon Tubular 50: rim and disc brakes

#### COLOR

# Hub Black Rim Carbon

## **OPTIONS**

Front axle options: QR9 & 15TA

Rim options: ETRTO 622X13
carbon clincher / 622 carbon tubular





BRAKES SUSPENSION WHEELS





#### **EUROPE: WEST/SOUTH**

Formula France E.U.R.L. 33 Chemin du souvenir français 06730 Saint Andre de la Roche FRANCE +33 493 139 840 **+** +33 492 090 613 servicefrance@formula-italy.com

#### **EUROPE: MIDDLE/EAST/NORTH**

Formula Deutschland Gmbh Hochstätt 12 83253 Rimsting GERMANY +49 (0) 8054 908 908 0 +49 (0) 8054 908 908 10 servicegermany@formula-italy.com

#### **NORTH AMERICA**

Formula North America Inc. 414 Hwy 21 Bypass Fort Mill, SC 29715 **L** +1 (803) 547 7010 <del>+</del>+1 (803) 547 7040 serviceusa@formula-italy.com

#### CANADA

Formula Canada Motorcycle and Bicycle Italian Technology Inc. unit 107 - 20119 113b ave. V2X 071 MAPLE RIDGE B.C. **L** +1 604 459 0070 **1** +1 604 459 0070 servicecanada@formula-italv.com

#### **UNITED STATES**

Formula North America Motorcycle and Bicycle Technology Inc. 411 B Street Suite 6 Petaluma, CA 94952 +1 866 619 6660 infousa@formula-italy.com

#### **CORPORATE HEADQUARTERS: ITALY** FORMULA s.r.l

Via Erbosa, 63 | 59100 Prato +39 0574 603 609

**+39 0574 611 046** 

serviceitalia@formula-italy.com