

evolution towards lightness



| MASTER CYLINDER                                     |
|---|
| Forged radial master cylinder (M/C)                 |
| Patent-pending high capacity, integrated reservoir. |
| Removable handlebar clamp.                          |
| Flip-flop master cylinder assembly.                 |
| Dual M/C bleed ports for easy on-the-bike bleeds.   |
| Aluminum forged lever blade (carbon option).        |
| Laser etched logo.                                  |

| SPECIFICATIONS |   |
|----------------|---|
| M/C body:      | Anodized matte black  |
| Caliper body:  | Anodized matte black  |
| Lever blade:   | Forged aluminum, anodized silver  |
| Hose:          | Braided grey: 100 cm / 165 cm   |
| Rotor 1-piece: | 160 mm / 180 mm / 203 mm  |
| Brake-pad:     | Organic, w/aluminum back plate  |
| Mounting:      | Standard PM 6"  |
| Weight:        | 277 grams (PM - including 1000 mm hose, 160 mm rotor, complete hardware ) |



| CALIPER   |
|---|
| 1-piece patent-pending forged caliper body with 22 mm pistons.                                  |
| Post mount style caliper.   |
| Aluminum backed brake pads for additional weight saving.  |
| Top and bottom vented caliper body for maximum cooling and performance.                         |
| Patent-pending caliper cap / piston system aids in compact design and increased fluid capacity. |
| Laser etched logos.   |
| Top loading pads simplify pad changes.  |

| OPTIONS                   |   |
|---------------------------|---|
| Lever blade:              | Carbon, saves 6 g.  |
| Rotor 2-piece standard:   | 160 mm / 180 mm   |
| Rotor and mounting bolts: | Titanium rotor bolts save 10 g                            |
| Rotor 2-piece centerlock: | 160 mm / 180 mm   |
| Mounting:                 | Adapters available for IS/PM;<br>160 mm / 180 mm / 203 mm |
| FCS                       | Red or gold available                                     |
| Reach adjustment          | Red or gold knob  |
| Mixmaster                 | Available   |



| MASTER CYLINDER                                     |
|---|
| Forged radial master cylinder (M/C)                 |
| Patent-pending high capacity, integrated reservoir. |
| Removable handlebar clamp.                          |
| Flip-flop master cylinder assembly.                 |
| Dual M/C bleed ports for easy on-the-bike bleeds.   |
| Forged aluminum lever blade (carbon option).        |
| Laser etched logos.                                 |

| SPECIFICATIONS |  |
|----------------|--|
| M/C body:      | Anodized gloss black   |
| Caliper body:  | Anodized gloss black   |
| Lever blade:   | Forged aluminum, anodized black  |
| Hose:          | Black: 100 cm / 165 cm   |
| Rotor 1-piece: | 160 mm / 180 mm / 203 mm   |
| Brake-pad:     | Sintered   |
| Mounting:      | Standard PM 6"   |
| Weight:        | 307 grams (PM - including 1000 mm hose, 160 mm rotor, complete hardware) |





| CALIPER   |
|---|
| Patent-pending forged one-piece post mount caliper.               |
| Huge 24 mm caliper pistons for amazing power.                     |
| Top vented caliper allows for wheel on pad changes and eliminates |
| overheating effects.  |
| Bottom vented caliper pistons provide additional cooling.         |
| Laser etched logos.   |
| Top loading pads simplify pad changes.                            |

| XII AM MUN FR DH |
|------------------|
|------------------|

| OPTIONS                   |   |
|---------------------------|---|
| Lever blade:              | Carbon, saves 6 g.  |
| Rotor 2-piece standard:   | 160 mm / 180 mm   |
| Rotor and mounting bolts: | Titanium rotor bolts save 10 g                            |
| Rotor 2-piece centerlock: | 160 mm / 180 mm   |
| Mounting:                 | Adapters available for IS/PM;<br>160 mm / 180 mm / 203 mm |
| FCS                       | Red or gold available                                     |
| Reach adjustment          | Red or gold knob  |
| Mixmaster                 | Available   |





XC AM ENDURO FR DH

| CALIPER                                  |
|--|
| 1-piece caliper body with 22 mm pistons. |
| Post mount style w/adaptors.             |
| Top and bottom vented caliper body.      |
| Laser etched logo.                       |
| Top loading pads simplify pad changes.   |

| OPTIONS                   |  |
|---------------------------|--|
| Rotor 2-piece standard:   | 160 mm / 180 mm                                      |
| Rotor and mounting bolts: | Titanium rotor bolts save 10 g                       |
| Rotor 2-piece centerlock: | 160 mm / 180 mm                                      |
| Mounting:                 | Adapters available for IS/PM; 160 mm, 180 mm, 203 mm |
| FCS                       | Red or gold available                                |
| Reach adjustment          | Red or gold knob                                     |
| Mixmaster                 | Available  |



#### **FEATURES**

**TheONEFR** (freeride) copies the top features of its older brother while maintaining a value price. Our patented forged caliper with its large 24 mm pistons, provides the same stopping power and modulation, while radial one-piece cast master cylinder keeps the weight down.

**New for 2011:** upgrade your brakes with our new FCS (feeling control system), instant reach adjustment and Mixmaster. Parts only available from a Formula dealer.

| Minnase Services and the services are services and the services and the services and the services are services and the services and the services and the services are services and the services and the services are services and the services and the services are services are services and the services are services are services are services are services and the services are ser |
|--|
|--|


| MASTER CYLINDER                                     |
|---|
| Radial Master Cylinder.                             |
| Patent-pending high capacity, integrated reservoir. |
| Removable handlebar clamp.                          |
| Flip-flop master cylinder assembly.                 |
| Laser etched logo.                                  |

| SPECIFICATIONS |   |
|----------------|---|
| M/C body:      | Painted black   |
| Caliper body:  | Anodized matte black  |
| Lever blade:   | High tensile strength casting, painted silver                               |
| Hose:          | Black: 100 cm / 165 cm  |
| Rotor 1-piece: | 160 mm / 180 mm / 203 mm  |
| Brake-pad:     | Sintered  |
| Mounting:      | Standard PM 6"  |
| Weight:        | 346 grams (PM - including 1000 mm hose,<br>160 mm rotor, complete hardware) |



| CALIPER   |
|---|
| Patent-pending forged 1-piece post mount caliper.                 |
| Huge 24 mm caliper pistons for amazing power.                     |
| Top vented caliper allows for wheel on pad changes and eliminates |
| overheating effects.  |
| Bottom vented caliper pistons provide additional cooling.         |
| Laser etched logo.  |
| Top loading pads simplify pad changes.                            |

| OPTIONS                   |  |  |
|---------------------------|--|--|
| Rotor 2-piece standard:   | 160 mm / 180 mm                                      |  |
| Rotor and mounting bolts: | Titanium rotor bolts save 10 g                       |  |
| Rotor 2-piece centerlock: | 160 mm / 180 mm                                      |  |
| Mounting:                 | Adapters available for IS/PM; 160 mm, 180 mm, 203 mm |  |
| FCS                       | Red or gold available                                |  |
| Reach adjustment          | Red or gold knob                                     |  |
| Mixmaster                 | Available  |  |



## **DISC BRAKE DIAMETER**

1-Piece Rotor [all brakes]

Stainless steel

| Diameter [mm]  | 160 | 180 | 203 |
|----------------|-----|-----|-----|
| Weight [grams] | 87  | 121 | 160 |

## **DISC BRAKE DIAMETER**

1-Piece Rotor [all brakes] centerlock rotor

Stainless steel

| Diameter [mm]  | 160 | 180 | 203 |
|----------------|-----|-----|-----|
| Weight [grams] | 104 | 138 | 178 |



## **DISC BRAKE DIAMETER**

2-Piece Rotor [all brakes]

Stainless steel / aluminium

| Diameter [mm] | 160 | 180 |
|---------------|-----|-----|
| Weight [gram] | 95  | 115 |

## **DISC BRAKE DIAMETER**

2-Piece Rotor [all brakes] centerlock rotor Stainless steel / aluminium

| Diameter [mm] | 160 | 180 |
|---------------|-----|-----|
| Weight [gram] | 107 | 127 |

Formula France E.U.R.L. Tel: +33 (493)139840 Fax: +33 (492) 090613 formula5@orange.fr

#### **EUROPE: EAST / NORTH**

Formula Deutschland GmbH

Tel: +49 (8054) 902947 Fax: + +49 (8054) 902948 service@formula-brake.de

#### **NORTH AMERICA**

Formula N.A. Tel: +1 (850) 501.3145 cvogl@formula-brake.com

#### TAIWAN R.O.C

Formula srl Taiwan Branch Tel: +886 (4) 2359.7996 Fax: +886 (4) 23599259

# HEAD OFFICE: ITALY FORMULA s.r.I

Via Erbosa, 63 59100 Prato

Tel.: +39 (0574) 603.609 Fax: +39 (0574) 611.046 info@formula-brake.it



GLOBAL DISTRIBUTOR LIST www.formula-brake.com